



ORYX® Grafite FR

PRODUCT INFORMATION SHEET

Version 1.0, 14-03-2016 (English)

DESCRIPTION	ORYX® Grafite FR is an acrylic sealant that expands under pressure in the event of fire and creates a seal for plastic pipes (up to 55 mm diameter), plastic and steel pipes fitted with flammable insulation, and bundled cable penetrations.
APPLICATIONS	<ul style="list-style-type: none">- Small-diameter plastic pipes in fire-resistant walls- Around steel pipes with flammable insulation- Around steel pipes and other small penetrations, including cable bundles
CHARACTERISTICS AND FEATURES	Features of ORYX® Grafite FR include: <ul style="list-style-type: none">- Fire-resistant up to four hours- Maintains acoustic performance of the partition- Independently proven and tested to the requirements of EN 1366-3:2009- Outstanding adhesion to the most common surfaces, including porous materials, without the use of primers- Easy to use, water-based for rapid drying and easy cleaning- Can be painted when dry- Odourless and halogen-free- Creates smoke-tight and airtight seal
INSTRUCTIONS FOR USE	<ul style="list-style-type: none">- Surface to be sealed must be clean, dry and dust-free- Apply between +5°C and +30°C- Use mineral wool backing to control the joint depth- Ensure the opening is completely filled to the required depth- Finish the sealant with a dry trowel within five minutes of applying- Store in a cool, dry place at temperatures between +2°C and +30°C. Protect against frost
LIMITATIONS	It is the user's responsibility to determine the suitability of the product. We recommend making a test sample before use. ORYX® Grafite FR is not suitable for use underwater, such as in swimming pools or aquariums, or for applications in structural glazing, and it should not come into contact with food.
SAFETY REQUIREMENTS	For further information, please refer to the Safety Data Sheet <ul style="list-style-type: none">- In case of contact with eyes, rinse immediately with clean water and seek medical advice. Keep out of the reach of children. Do not swallow.- Irritating to eyes- Wear appropriate protective clothing, gloves and visors- Use in well-ventilated areas- Prevent contact with skin and eyes- Apply the applicable standards of industrial hygiene

Given that the product is used in circumstances beyond our control, ORYX cannot be held directly or indirectly liable.